



Cop-R-Tite Mastic

Asphaltic Based Flashing Mastic

DESCRIPTION:

This unique fibrated mastic was developed to insure the proper sealing characteristics of copper laminated flashings. Cop-R-Tite Flashing Mastic is a compounded composition of asphalt, mineral stabilizers, and interfibe. It is manufactured to a trowel grade consistency which will provide a durable, elastic coating highly resistant to weathering while providing excellent adhesion properties. Cop-R-Tite Flashing Mastic performs well over a wide range of temperature and weather conditions. It complies with all requirements of Federal Specifications SS-C-153, Type 1 and ASTM D2822, Type 1 and SSPC No. 12.

Physical Properties:

USES:

Copper Laminated Flashings.

Splicing

Cop-R-Tite Flashing Mastic is the preferred mastic to be used while splicing copper flashings. Material should be overlapped a minimum of 4" and a coating of Cop-R-Tite applied to yield a 30sf per gallon coverage.

Vertical Masonry Surfaces

Cop-R-Tite Flashing Mastic should be spotted to vertical surfaces to receive flashing. Cop-R-Tite will hold the flashing in place while masonry is set. Flashing should be secured in a reglet or masonry joint or mechanical fastener.

General Purpose

Cop-R-Tite can also be used as a general purpose cement for repairing leaks in asphalt roofs, metal roofs, chimneys, flues, down spouts and concrete.

CONSISTENCY:

Cop-R-Tite Mastic is a heavy, trowel grade which spreads easily and adheres to most surfaces. Coverage should yield approximately 30 sf per gallon. Cop-R-Tite retains its elasticity and ductility, thus coating will resist extreme variations in temperature.

SURFACE PREPARATION:

All surfaces should be clean, dry, and free from grease, oil, or other loose foreign matter.

PACKAGE SIZE:

Available in 5 gallon pails and 30 oz. tubes.

Physical Properties:

Boiling Point	650°F
Flash point and method	110°F
Solubility in water	None
Appearance	Black Paste

P.O. Box 98, Springvale, ME 04083
 Tel: 1-800-252-2306 or 1-207-490-2306
 Fax: 207-490-2998
 E-mail: info@advancedflashing.com

www.advancedflashing.com