



P.O. BOX 98, SPRINGVALE, MAINE 04083
TEL. 1-800-252-2306 or 1-207-490-2306
FAX 207-490-2998
www.advancedflashing.com

PRIMER SEAL

LOW VOC WATERPROOFING PRIMER

DESCRIPTION:

Primer Seal is a high quality, rubberized, low VOC primer, formulated for the professional waterproofing contractor.

TYPICAL USES:

This quick dry, high-tack primer provides maximum bond to asphalt, concrete, masonry and metal surfaces.

APPLICATION:

Apply with a long nap roller or spray equipment at the rate of 250 to 300 square feet per gallon. Allow to cure until the surface is tacky, but will not transfer when touched. Primer should be allowed to dry a minimum of 1 hour, and a maximum of 8 hours. Do not thin with organic solvents.

TYPICAL PHYSICAL PROPERTIES*

Property	Results
Weight per Gallon	7.53 lbs
Solids Content	38% by weight
Tack Free Time	30 min. @ 75°F
VOC	Less than 450 grams/litre
Flash Point	<68°F
Packaging	5 Gallon pails

*All values stated as nominal at time of manufacture.

SAFETY:

For safety, health, and handling information contact Advanced Building Products at 1-800-252-2306 for Material Safety Data Sheets (MSDS).

LIMITED WARRANTY

Advanced Building Products, Inc. warrants this product to be free of defects in workmanship and materials only at the time of shipping from our factory. If any Advanced Building Products materials prove to contain manufacturing defects that substantially affect their performance, Advanced Building Products will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by Advanced Building Products with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Advanced Building Products specifically disclaims liability for any incidental, consequential, or other damages including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Advanced Building Products liability and buyer's remedy under their limited warranty shall not exceed the purchase price of the Advanced Building Products material in question.